

Ethernet-based, Modular Media Converter Chassis

MediaConverter/8

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Supports Ethernet, Fast Ethernet and Gigabit Ethernet
- Supports “Mc” modules
- Table-top and rack-mountable
- 8-slot chassis
- Internal AC power
- Modular, hot-swappable architecture reduces operational costs associated with product installation, upgrades and maintenance

The unmanaged B+B SmartWorx' MediaConverter/8 to install compact, horizontal modules that support speeds of 10/100Mbps, 100Mbps or gigabit. The eight slot chassis is one of four chassis that can provide a low-cost solution for segments in a network that require a copper to fiber conversion.

The modules available from B+B SmartWorx for this chassis are the McLIM, McLIM-TP-TX/FX and McGigabit.

The eight slot chassis has a reliable internal AC power supply, and a country-specific power cord is shipped with each chassis.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
MediaConverter/8	
851-10908	8 Slot, AC Chassis

All product specifications are subject to change without notice.
MediaConverter-8_4117ds

Ethernet-based, Modular Media Converter Chassis

MediaConverter/8



SPECIFICATIONS

TECHNICAL

8-slot chassis to house the following modules:

McLIM, McLIM 10/100, McGigabit

Fits into a 19" Rack

MECHANICAL

Dimensions 4.54H x 44.19W x 12.7D cm

1.79H x 17.4W x 5.0D in

Shipping Weight 2.8 kg (6.25 lbs)

POWER

120/240 VAC, 50/60Hz, 1A/0.5A

ENVIRONMENTAL

Operating Temperature – DC Terminal Block 0° to +50° C (+32° to +122° F)

Storage Temperature -25° to +70° C (13° to +158° F)

Operating Humidity 5% to 95% (non-condensing), 0 – 10000 ft. altitude

REGULATORY APPROVALS

FCC Class A, UL/CUL, CE, CSA

MECHANICAL DIAGRAM

units - inches

