



N-07-50-MH-9-C-XX

ⓓ

N = CABLE TIES

CABLE TIE LENGTH  
INCHES  
(ROUNDED)

TENSILE STRENGTH  
18 = 18 LBS  
40 = 40 LBS  
50 = 50 LBS  
120 = 120 LBS

TIE TYPE  
(BLANK) = STANDARD TIE  
ID = IDENTIFICATION  
MH = MOUNTING HOLE

INTERNAL DESIGNATOR

AMOUNT PER PACKAGE  
C = 100  
D = 500  
M = 1000

COLORS  
0 = UV BLACK  
9 = NATURAL  
30 = HEAT STABILIZED

SALES DRAWING

REMOVE BASE INFO EC NO: ETC2007-0295 DRWN: TBOANN02007/02/13 CHKD: JMACNEIL 2007/02/13 APPR: JMACNEIL 2007/02/14	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY
	DESCRIPTION	mm	INCH	DIMENSION STYLE IN/MM		TITLE	
	▽ = 0	4 PLACES ± --- ± ---	3 PLACES ± --- ± ---	DRAWN BY B.ENDERL	DATE 04/05/11	19252 SERIES ENGINEERING NUMBERS CABLE TIES	
	∇ = 0	2 PLACES ± --- ± ---	1 PLACE ± --- ± ---	CHECKED BY H.BEITZL	DATE 04/05/11	MOLEX INCORPORATED	
REV	ANGULAR ± ---°	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY R.DEROSS	DATE 04/05/11	MATERIAL NO. SEE CHART	DOCUMENT NO. SD-19252-001
				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			