



Part. No. for plug connector	
UNC 4-40	M3
16-000990	16-000940

NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. THREADED INSERT: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
3. COLLAR: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
4. JACKSCREW: STEEL; NICKEL PLATED
5. WIRE ROPE: STAINLESS STEEL 1.4401
6. RETAINING WASHER: STAINLESS STEEL 1.4122
7. TERMINAL RING: UNINSULATED, COPPER ALLOY; min. 200µinTIN over 80µin NICKEL
8. MAXIMUM TORQUE VALUE FOR THREAD: 6in.LB
9. CONNECTOR IS PART MARKED: PART NO. CONEC ABC

Directive 2002/95/EC
"RoHS"
Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		 dim. in mm	scale:		2:1 (5:1)	
	ISO 2768-m			material:		SEE NOTES	
	date		name		title:		SCREEN CAP 50pos. FOR PLUG CONNECTOR with threaded insert, jackscrew and wire rope
	drawn	17.11.08	Petker	dwg no:		Inventor 10	
appd.	17.11.08	Fischer	part no:		16K1A2400		
norm				DIN-A3		sh: 1	
d-old				part no: see table			
a Origin		CONEC ®					
rev.	description	date	name				