




APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	VOLTAGE		APPLICABLE CABLE	CABLE DIAMETER : $\phi$ 8.3~9.3	
	CURRENT				
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
					
REMARK			APPROVED	A0. SUZUKI	09. 05. 11
THIS PRODUCT SHALL BE MATED WITH DH30B-37S, IT APPLIES TO DH30B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.  Unless otherwise specified, refer to JIS C 5402.			CHECKED	KN. ICHIKAWA	09. 05. 11
			DESIGNED	MO. SHIMOYAMA	09. 05. 11
			DRAWN	MO. SHIMOYAMA	09. 05. 11
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test		
	SPECIFICATION SHEET		PART NO.	DH-37-CT2B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0049-0-00	 1/1